

HOW TO RIG A BIG HAMMER™ SWIMBAIT

Page 1

- Step 1)** Start by holding the jig head up to the swimbait as if it were rigged. Note where the hook should come out of the back of the swimbait.
- Step 2)** Using the point of the hook mark the back of the swimbait where the hook should come out.
- Step 3)** Hold the jig head up to the swimbait again, this time slightly forward. Note where the hook should enter the front of the swimbait so that the top of the swimbait is flush with the top of the jig head.



STEP 1



STEP 2



STEP 3

- Step 4)** Push the hook into the front of the swimbait slightly. Turn the swimbait so that you are looking directly at the back of the bait. Looking at the swimbait from this direction will help you rig it straight.
- Step 5)** Slide the swimbait on the jig head and stop just when the hook starts to come out of the mark you made in the back of the swimbait. If possible, do this in one motion as stopping and starting may cause crooked rigging. It is best to try and grab the swimbait where the hook has already gone through. This will help eliminate crooked rigging due to squeezing of the swimbait.
- Step 6)** Make a mental note of the distance between the back of the bait keeper on the jig head and the front of the swimbait. Remembering this distance will allow you to skip Step 2 the next time you are rigging a swimbait on that size jig head.



STEP 4



STEP 5



STEP 6

HOW TO RIG A BIG HAMMER™ SWIMBAIT

Page 2

Step 7) Continue to push the swimbait on to the jig head. If you are planning to glue the swimbait to the jig head stop when the back of the jig head is about 1/8 of an inch from the front of the swimbait. Add a drop of glue and finish rigging.



STEP 7